



MODIFIKASI AMBULANCE SUZUKI APV TYPE MEDIUM LKPP

EXTERIOR & INTERIOR MODIFICATION



- A. Fixed Central Gas System
- 2 Pcs Oxygen Cylinder 1M³
 - 2 Pcs Oxygen Regulator
 - 2 Pcs Neple Elbow
 - 1 Pcs Oxygen Wall Outlet
 - 1 Pcs Nasal Oxygen Cannula for Adult
 - 1 Pcs Oxygen Mask for Adult
 - 1 Set Oxygen Alarm Indicator
 - High Pressure Hose and Hose Clamp
 - 1 Set Oxygen Valve On / Off
 - Tubing High Pressure and Clamp Tubing
 - 1 Pcs Flowmeter Oxygen with Humidifier
- B. Attendant seat with box space for equipment
(Bahan Jok : Multi Flex dilapis ABS Cetak dengan Jok Cetak)
- C. Medical Equipment Compartment system with acrylic door, including Washtafel cabinet with 2 water tank, finishing duco
- D. Seat for Medical Officer Facing back (Medical Seat)
- E. Bumper Protection for Ambulance Stretcher
Material : Plate Stainless Steels
- F. Sliding Infuse Materials : Stainless Steels
- G. Three Extra DC Outlets
- H. One Extra AC Outlets
- I. Floor Modification Vinyl Covering AntiBacteria
- J. LED Flash light bar include coil Filter
- Length: 120 cm, Width: 30 cm, Height: 22cm
 - Input Voltage 12 Volt
 - Life Time 10.000 Hours
- Multi Sound Sirene System Include Microphone Paging
- Police Voice, Ambulance Voice & Fire Voice
 - Input Voltage 12 VDC
 - Current Input 7.5 Ampere
 - Power Output 500 Watt
- K. Adjustable Lighting spot light, 1 pcs
- L. Adjustable Examination Lamp, 2 pcs
- M. Base Stretcher Full Stainless Steels with space for Scoop Stretcher
- N. Locking and Unlocking key for Stretcher
- O. Fire extinguisher 1 kg with Bracket
- P. Sticker & Logo Standard
- Q. Curtain (Tirai) Cabin & Patient
- R. Glass Film 60 / 80 %
- S. Ambulance Stretcher Roll in Cot
- Features and Benefits
- Tubular aluminium construction provides durability & strength.
 - Automatic locking leg system ensures that the cot legs are locked into place once they are fully unfolded.
 - Adjustable bracket angle from 0 to 75 allows patient to be in the most comfortable position possible during transport.
 - Patient restraint system ensures safety of patient during transport.
- Specification :
- | | |
|-------------------------------|--------------------------|
| Length | : 197 cm |
| Width | : 58 cm |
| Height Maximum | : 101 cm |
| Height Minimum (lowest level) | : 26 cm |
| Gross Weight | : 47 kg |
| Net Weight | : 40 kg |
| Castor | : 8 Pc Swivel |
| | : 2 Pc Swivel with break |
- Accessories :
- Safety Belts : 3 Pc
 - Mattress : 1 Pc
- T. Folding Scoop Stretcher
- Dimension :
- Max. Length : 227 cm
 - Length as folded : 122 cm
 - Length: 169 cm, Width : 42 cm, Height : 7 cm
 - Max. Load : 160 kg
 - Accessories : 3 Safety Belt
 - Material : - Aluminium
 - Nylon Fiber
 - Finishing : Powder Coating
- U. Gel Desinfectant / Antiseptic with Bracket